

# Cooling and Straining Tank

VP15

- > used in commercial Laundromats.
- > the function of a cooling and straining tank is to slow the flow of warm/hot waste water, thus allowing it to cool before flowing out to sewer. The primary tank chamber has a removable basket that traps lint and hair.

Dimensions mm				
Capacity litres	A	B	C	D
<b>Above-ground</b> Polypropylene				
250	1000	600	450	800
400	1500	600	450	800
600	1500	750	550	900
1000	2000	750	650	1000
<b>Below-ground</b> Polypropylene				
250	1250	450	450	850
400	1400	600	500	900
600	1400	750	570	970
1000	1900	750	700	1100
1500	1900	900	900	1300
2000	2400	900	950	1350

## Cooling and Straining Tank model VP15

- > Manufactured in Polypropylene materials.
- > Above-Ground tanks are supplied with removable access covers
- > Below-Ground tanks should be fitted with access covers (supplied separately) capable of being removed by one man
- > Inlet and outlet pipes are 100mm nb.
- > Tank dimensions and pipework positions are nominal and in all cases conform to Trade Waste recommendations
- > When space limitations dictate, equivalent capacity tanks can be manufactured to order
- > \*Note: Above-ground tanks larger than 250 litres capacity have external bracing fitted. Allow 50mm all round

## Other products available

- > Grease Interceptors for above and below-ground installations
- > Mixing Tanks
- > Settling Tanks (Plaster Trap)
- > Testing Sump
- > Solvent and Oil Interceptor
- > Petrol and Oil Interceptor
- > Water Storage Tanks
- > Custom Fabrication to order
- > Laboratory Sinks
- > Pot Sinks

